

109954 & 109955

Specimen Label

GREEN LAWNGER

Turf Paint and Divot Mix Colorant

Green Lawnger restores the natural green color to turf during dormant periods. Green Lawnger may also be pre-applied to divot mix sand, giving the mix a natural green color. Green Lawnger contains no hazardous chemicals, heavy metals, or other inert ingredients known to be harmful to turf.

DIRECTIONS

Before applying Green Lawnger, cut turf to desired height. One gallon (3.78 liters) of Green Lawnger will cover 4,000-12,000 square feet (370-1115 m²) of turf. Use at a rate of 1-2 gallons (3.78-7.56 ltrs) of spray solution per 1,000 square feet (41-82 ml/m²). The area covered will vary with the rate of Green Lawnger used, type and condition of grass being treated, and turf color desired. Green Lawnger may also be tank mixed with fungicides and herbicides. Check manufacturer's label for appropriate usage rates.

Dormant Application

Dilute one gallon (3.78 liters) of Green Lawnger with 7 to 9 gallons (26-34 liters) of water. For a darker turf color, reduce the volume of water. Some experimentation may be required with the water to colorant ratio to obtain the exact color desired. Green Lawnger's color will last the entire dormant season.

Non-Dormant Application

Dilute one gallon (3.78 liters) of Green Lawnger with 15 to 20 gallons (56-75 liters) of water and apply over 9,000-12,000 square feet. (8 oz Green Lawnger with 120 to 160 oz of water per 1,000 sq. ft.) Again, the application rate depends on the desired color. For best results on any discolored area, two applications of a higher dilution are recommended to blend the colored area in with the surrounding healthy turf.

Divot Mix Sand

Mix 6 ounces (177 ml) of Green Lawnger with the same volume of water. Spray or pour the solution onto 100 lbs (45 kg) of divot mix sand in a cement-type mixer. Mix until colored. Adjust the colorant to water ratio to achieve the desired color.

For best results, use low to medium sprayer pressure. Avoid overspray on concrete, masonry, or any other objects where color is not desired. Permanent staining may occur. Accidental overspray may be removed by a water rinse prior to drying. To prevent rub-off on uniforms, allow Green Lawnnger to dry prior to using athletic field. Rinse spray tank, spray nozzles, and screens thoroughly with water immediately following use.

If this product is mixed with pesticides, the entire mixture, including rinsate, must be handled and disposed of according to all applicable local, state, and federal guidelines.

Equipment Notice: Becker Underwood recommends the use of Teflon seals to aid in the prevention of leaks when using Green Lawnnger in centrifugal pumps. Standard ceramic seals may leak during operation.

Caution

Keep out of the reach of children. Do not take internally. In case of eye contact, flush with large amounts of water and consult a physician. In case of ingestion, dilute with water or milk and consult a physician. Do not re-use this container. Rinse contents into the spray tank and crush prior to disposal. Do not apply to food or feed crops or grain after harvest. A spray shield is recommended for applications if overspray or drift is a potential problem. EMERGENCY CONTACT: CHEMTREC 1-800-424-9300

Notice: There are no warranties which extend beyond the description on the label hereof. The manufacturer, Becker Underwood, Inc., warrants this product to be as described on the label. The manufacturer's liability on this warranty is limited to return of the purchase price of this product. The buyer assumes all risks and liability resulting from the use of this product, whether used singly or in combination with other goods. The manufacturer neither assumes nor authorizes any person to assume for it any other liability in connection with the sale or use of this product.

Green Lawnnger is a registered trademark of Becker Underwood, Inc.

manufactured by:

Becker Underwood, Inc.

801 Dayton Avenue
Ames, IA 50010
515-232-5907
Fax 515-232-5961
www.bucolor.com