



PRODUCTS • Utility & Multi Products • LT2000 2,000lbs



165577



LT2000 Utility 2,000 lb./907 kg

1220210 12VDC with freespooling



LT2000

Utility

Standard Features

- Powers Load In and Power Out
- Differential Planetary
- Pull and Turn Freespooling Clutch
- Low Amp, Permanent Magnet Motor
- Circuit Breaker Protected
- Heavy Duty Latched Hook with Rope Thimble
- Sealed, Handheld Switch

Not recommended for ATV snowplow application.

Performance 12VDC (Bottom Layer)

Line Pull lbs./kg	Line Speed FPM (m/m)	Motor Amps 12V
0	10.0 (3.0)	10
500 (227)	8.0 (2.4)	25
1,000 (454)	6.5 (2.0)	50
1,500 (680)	4.8 (1.4)	70
2,000 (907)	2.5 (0.8)	100

Specifications

Rated Line Pull (Bottom Layer)	2,000 lb. (907 kg)
Motor	1.0 hp (0.8kW) PM Motor, 12V DC
Gearing	Differential Planetary
Gear Ratio	153:1
Freespooling Clutch	Pull and Turn Action
Wire Rope	5/32" x 49' (3.9mm x 15m)
Dimensions	11.0" l. x 4.1" d. x 4.1" h. (285mm l. x 105mm d. x 105mm h.)
Drum Diameter	1.25" (31.8mm)
Drum Length	2.83" (72.0mm)
Installed Weight	12.0 lb (5.4 kg)
Ship Weight	17.6 lb (8.0 kg)

Switching Method	Handheld Remote
Switching Mechanism	Direct Switch
Roller Fairlead	Optional
Color-Coded Wiring	Yes

Recommended Accessories

Roller Fairlead	1560C
Pulley Block	2227A
2"x 6' Tree-Saver Strap	1509
2"x 20' Tree-Saver Strap	2517
1"x 8' Tree-Saver Strap	2302284
ATV Bow Shackles	2302285
ATV Handlebar Switch Upgrade Kit	2320200



ATV Accessory Kit	2302001
-------------------	---------



Replacement Parts

Wire Rope	1535C
Kit-Switch	2320200
Circuit Breaker	87-10799
Remote Control Handheld	87-12869

Dimensions

