

2300N Series

N95 PARTICULATE RESPIRATORS

Available in three sizes.

Exhale valve lets workers breathe easy and stay cool.

Dura-Mesh® shell resists collapsing in heat and humidity.

Molded nose bridge seals easily and comfortably without a metal noseband.

Facepiece is naturally contoured without pressure points.

Soft, foam nose cushion for added comfort.

Softspun® lining for increased comfort and durability.


Suitable for most welding applications.

Flame-retardants added to decrease flammability of shell.

2300N95 – Medium/Large

2301N95 – Small

2307N95 – Low Profile



Medium/Large



Low Profile



Small

STAY COOL ON THE JOB.

Workers stay cooler with an exhale valve that reduces hot air build up. There's less breathing resistance. And workers don't have to break midshift to cool off.

EASY FIT, MORE COMFORT.

The molded nose bridge with soft foam nose cushion provides the wearer an easy, comfortable fit. There's no metal noseband to adjust. And the seal is maintained without pressure points.

LAST LONGER, USE FEWER.

The Dura-Mesh® shell protects the filter media so it stays cleaner-looking longer. The shell resists collapsing, even in heat and humidity. So the respirator holds its shape longer. The result is fewer respirators used and lower costs.

FIT MORE WORKERS.

Available in three sizes to fit more workers and increased OSHA compliance. Use #2300N95 (M/L – blue straps) for most workers. For smaller faces #2301N95 (S – white straps) and #2307N95 (low profile – green straps) for rounder facial features.

SUITABLE FOR WELDING.

2300N Series Particulate Respirators are suitable for most welding applications. Moldex's Dura-Mesh® shell resists collapsing in hot humid conditions common to most welding applications. Plus, flame retardants added to shell help reduce flammability.

MOLDEX TECHNICAL SERVICE.

Moldex provides technical assistance including help with fit testing, *How To Set-Up Your Respiratory Protection Program* plus a Toll-Free Technical Help line. Just call 800/421-0668 ext. 550 or 310-837-6500 ext. 550.

N95 PARTICULATE RESPIRATORS

2300N Series

2300N95 – Medium/Large
2301N95 – Small
2307N95 – Low Profile

APPLICATIONS

⚠ WARNING TO USER:

Follow all instructions and warnings on the use of this respirator and wear during all times of exposure. Failure to do so will reduce respirator effectiveness, wearer protection and may result in sickness or death.

Before use, the user must first be trained by the employer in proper respirator use, in accordance with applicable safety and health standards, for the contaminant and exposure level in the assigned work area.

The particulates and other contaminants which can be dangerous to your health include those which you cannot see, taste, or smell.

This product has not been sold with warnings or use instructions for personnel involved in healthcare or related situations, where there may be the possibility of contact with disease or biological hazards. If you are considering such uses, first call the Moldex Technical Service Dept., 310/837-6500 ext. 550 or 800/421-0668 ext. 550.

USE AGAINST:

1. Particulate aerosols free of oil.

DO NOT USE AGAINST:

1. Concentrations of contaminants which are unknown or are immediately dangerous to life or health.
2. Concentrations of particulates which exceed the maximum use concentration or 10 times the OSHA Permissible Exposure Limit, whichever is lower.
3. Gases, vapors, asbestos, paint spray, sandblasting or particulate materials which generate harmful vapors.
4. Oil-based mists.

RESTRICTIONS:

1. This respirator does not supply oxygen and must not be used in atmospheres containing less than 19.5% oxygen.
2. Do not remain in contaminated area if any physical distress occurs, for example breathing difficulty, dizziness or nausea.
3. Leave contaminated area and replace respirator if it is damaged, distorted, a proper fit can not be obtained or breathing becomes difficult.
4. Do not alter, modify, or abuse this respirator.
5. Store unused respirators in box in a clean, dry, non-contaminated area.
6. Dispose of respirator according to your employer's policy and local regulations.
7. Dispose no later than thirty days after first use.
8. Use respirator before the "use by" expiration date printed on box.

LIMITED WARRANTY

IMPORTANT NOTICE TO PURCHASER

This limited warranty is made in lieu of the warranties of merchantability, fitness for particular purposes and all other warranties, express or implied. There are no other warranties which extend beyond the description on the face hereof. The physical standards and specifications of Moldex will be met by products sold.

Exclusive Remedies: damages for the breach of this limited warranty are limited to the replacement of such quantity of Moldex products proved to be defectively manufactured. Except as provided above, Moldex shall not be liable or responsible for any loss, damage, or liability, direct, indirect, incidental, special, or consequential, arising out of sale, use, or misuse, or the inability to use products by the user.


MOLDEX-METRIC, INC.

10111 W. Jefferson Blvd.
Culver City, CA 90232
800/421-0668 310/837-6500
FAX 310/837-9563

www.moldex.com e-mail: sales@moldex.com
Moldex, Dura-Mesh and SoftSpun are registered trademarks
The Mesh Design is a trademark of Moldex.
U.S. Patents #D285,374, #4,850,347, #4,384,577.
Made in the U.S.A. 9700-771 REV G 9/05




NIOSH LABEL



DEPARTMENT OF HEALTH & HUMAN SERVICES
USA

MOLDEX/METRIC INCORPORATED
CULVER CITY, CALIFORNIA, U.S.A.
800/421-0668



NIOSH

THESE RESPIRATORS ARE APPROVED ONLY IN THE FOLLOWING CONFIGURATIONS

TC-	PROTECTION ¹	RESPIRATOR			CAUTIONS AND LIMITATIONS ²
		2300N95	2301N95	2307N95	
84A-0328	N95	X		X	A B C J M N O P
84A-2455	N95		X		A B C J M N O P

1. Protection

N95 Particulate Filter (95% filter efficiency level) effective against particulate aerosols free of oil; time use restrictions may apply.

2. Cautions and Limitations

A- Not for use in atmospheres containing less than 19.5 percent oxygen.
 B- Not for use in atmospheres immediately dangerous to life or health.
 C- Do not exceed maximum use concentrations established by regulatory standards.
 J- Failure to properly use and maintain this product could result in injury or death.
 M- All approved respirators shall be selected, fitted, used, and maintained in accordance with MSHA, OSHA, and other applicable regulations.
 N- Never substitute, modify, add, or omit parts. Use only exact replacement parts in the configurations as specified by the manufacturer.
 O- Refer to user's instructions, and/or maintenance manuals for information on use and maintenance of these respirators.
 P- NIOSH does not evaluate respirators as surgical masks.

TECHNICAL HELP LINE

For information, technical assistance, and training materials call 800/421-0668 ext. 550 or 310/837-6500 ext. 550.

PACKAGING

10 Respirators per Box
10 Boxes per Case
100 Respirators per Case

WARNING

Failure to follow all instructions and warnings in the proper use of this respirator may reduce respirator effectiveness, wearer protection and may result in sickness or death. For additional information consult your supervisor, read all information on box and phone 800/421-0668 ext. 550 or 310/837-6500 ext. 550.

DISTRIBUTED BY:

In Canada:

Pacesetter Sales & Associates
20 Arthur Hall Drive
Sharon, ON L0G 1V0
Tel: 905/478-8042 Fax: 905/478-8010
www.pacesettersales.com