

B & B Battery (U.S.A.), Inc.

MSDS4088

6414 Randolph Street, City of Commerce, CA 90040 (323) 278-1900 Fax (323) 278-1268

Page 1 of 3

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Sealed Maintenance free Lead Acid Batteries

DATE: 9/1/05 ISSUED BY: ENGINEERING TELEPHONE NO: (323) 278-1900

HAZARDOUS COMPONENTS

COMPONENTS	%WEIGHT	TLV	LD50 ORAL	LC50 INHALATION	LC50 CONTACT
Lead (Pb, PbO ₂ , PbSo)	About 70%	N/A	(500) mg/Kg	N/A	N/A
Sulfuric Acid	About 20%	1 mg/m ³	(2.140) mg/Kg	N/A	N/A
Fiberglass Separator	About 5%	N/A	N/A	N/A	N/A
Styron R 478 (Polystyrene)	About 5%	N/A	N/A	N/A	N/A

PHYSICAL DATA

COMPONENTS	DENSITY	MELTING POINT	SOLLUBILITY (H ² O)	ODOR	APPEARANCE
Lead	11.34	327.4°C (Boiling)	None	None	Sliver-Gray Metal
Lead Sulfate	6.2	1070°C (Boiling)	40 mg/l (15°C)	None	White Powder
Lead Dioxide	9.4	290°C (Boiling)	None	None	Brown Powder
Sulfuric Acid	About 1.3	About 114°C (Boiling)	100%	Acidic	Clear Colorless Liquid
Fiberglass Sep.	N/A	N/A	SLIGHT	TOXIC	WHITE FIBROUS GLASS
478 Polyslyrene	N/A	N/A	NONE	NO ODOR	SOLID

FLAMMABILITY DATA

COMPONENTS	FLASHPOINT	EXPLOSIVE LIMITS	COMMENTS
Lead	None	None	
Sulfuric Acid	None	None	
Hydrogen		4% - 74.2%	Sealed batteries can emit hydrogen only if over charged (fload voltage> 2.4 VPC)
Fiberglass Sep.	N/A	N/A	Toxic vapors may be released. In case of fire: wear self-contained breathing apparatus.
478 Polyslyrene	None	N/A	Temperatures over 300 °C (572°F) may release combustible gases. In case of fire: wear positive pressure self-contained breathing apparatus.

FIRST AID**SULFURIC ACID PRECAUTIONS****SKIN CONTACT:** Flush with water, see physician if contact area is large or if blisters form.**EYE CONTACT:** Call physician immediately and flush with water until physician arrives.**Ingestion:** Call physician. If patient is conscious, flush mouth with water, have the patient drink milk or sodium bicarbonate solution.**DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON.****REACTIVITY DATA**

COMPONENT	Sulfuric Acid
STABILITY	Stable at all temperatures
POLYMERIZATION	Will not polymerize
INCOMPATIBILITY	Reactive metals, strong bases, most organic compounds
DECOMPOSITION PRODUCTS	Sulfuric dioxide, trioxide, hydrogen sulfide, hydrogen
CONDITIONS TO AVOID	Prohibit smoking, sparks, etc. from battery charging area. Avoid mixing acid with other chemicals.

6414 Randolph Street, City of Commerce, CA 90040 (323) 278-1900 Fax (323) 278-1268

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Sealed Maintenance free Lead Acid Batteries

DATE: 9/1/05 ISSUED BY: ENGINEERING TELEPHONE NO: (323) 278-1900

SPILL OR LEAK PROCEDURES

STEPS TO TAKE IN CASE OF LEAKS OR SPILLS

If sulfuric acid is spilled from a battery, neutralize the acid with sodium bicarbonate (baking soda), sodium carbon (soda ash), or calcium oxide (lime).

Flush the area with water discard to the sewage systems. Do not allow unneutralized acid into the sewage system.

WASTE DISPOSAL METHOD:

Neutralized acid may be flushed down the sewer. Spent batteries must be treated as hazardous waste and disposed of according to local state, and federal regulations. A copy of this material safety data must be supplied to any scrap dealer or secondary smelter with battery.

PROTECTION

EXPOSURE	PROTECTION	COMMENTS
SKIN	Rubber gloves, Apron	Protective equipment must be worn if battery is cracked or otherwise damaged.
RESPIRATORY	Respirator (for lead)	A respirator should be worn during reclaim operations if the TLV exceeded.
EYES	Safety goggles, Face Shield	

ELECTRICAL SAFETY

Due to the battery's low internal resistance and high power density. High levels of short circuit can be developed across the battery terminals. Do not rest tools or cables on the battery. Use insulated tools only.

Follow all installation instruction and diagrams when installing or maintaining battery systems.

HEALTH HAZARD DATA

LEAD: The toxic effects of lead are accumulative and slow to appear. It affects the kidneys, reproductive, and central nervous system.

The symptoms of lead overexposure are anemia, vomiting, headache, stomach pain (lead colic), dizziness, loss of appetite, and muscle and joint pain. Exposure to lead from a battery most often occurs during lead reclaim operations through the breathing or ingestion of lead dusts and fumes.

THIS DATA MUST BE PASSED TO ANY SCRAP OR SMELTER WHEN A BATTERY IS RESOLD.

SULFURIC ACID: Sulfuric acid is a strong corrosive. Contact with acid can cause severe burns on the skin and in the eyes.

Ingestion of sulfuric acid will cause GI tract burns. Acid can be release if the battery case is damaged or if the vents are tampered with.

FIBERGLASS SEPARATOR: Fibrous glass is an irritant of the upper respiratory tract, skin and eyes. For exposure up to 10F/CC use MSA Comfoll with type H filter. Above 10F/CC up to 50F/CC use Ultra-Twin with type H filter.

This product is not considered carcinogenic by NTP or OSHA.

B & B Battery (USA) Inc.

6415 Randolph St.,
City of Commerce, Ca 90040
Tel: (323) 278-1900
Fax: (323) 278-1268

Page 3 of 3

9/1/05

To: Customer of B & B Battery (USA) Inc. BP Series Batteries.

Subject: Transportation requirements in accordance with the Department of Transportation (D.O.T.)/ International Air Transport Association (I.A.T.A.) dangerous goods regulations as applied to B & B Battery BP Series Maintenance Free rechargeable sealed lead acid batteries.

We hereby certify that all B & B Battery BP Series Maintenance Free rechargeable sealed lead acid batteries conform in the UN2800 classification as " Batteries, wet, Non- Spillable, electric storage."

We further certify that under (I.A.T.A.) Dangerous Goods Regulation, 41st edition, UN2800 provision A67 and the (D.O.T.), CFR 49 Section 173.159 paragraph d., B & B Batteries having met the related conditions are EXEMPT from hazardous goods regulations, and therefore are unrestricted for Transportation by any means. Batteries must be protected so as to prevent short circuit, and must be securely packaged, and containers must be labeled " Non- Spillable" or " Non- Spillable Battery."

For your reference:

IATA Dangerous Goods Regulation,41th edition, Section 4.4 Special Provisions:

Non-Spillable batteries are considered to be Non-dangerous if at temperature of 55 deg. C (130 deg. F), the electrolyte will not flow from a ruptured or cracked case and there is no free liquid to flow and if, when packaged for transport, the terminals are protected from short circuit.

B & B Battery (USA) Inc.

RECHARGEABLE BATTERY RECYCLE NOTICE

Some states and cities have enacted laws related to the proper disposal of Rechargeable batteries. In an effort to reduce the amount of rechargeable batteries being disposed of as solid waste we are required to notify you of recycling opportunities where there is no cost to you.

The Rechargeable Battery Recycling Corporation (RBRC) is an organization funded by rechargeable battery manufacturers whose mission is to implement programs to collect rechargeable batteries for recycling. For more information on how to recycle your rechargeable batteries, at no cost to you, please visit the web site listed below.

This Rechargeable Battery law does not apply to household alkaline batteries, watch or hearing aid button batteries or automobile batteries.

www.call2recycle.org