


| | | | |
|---------------------------------------|------------------------|--|---|
| MATERIAL SAFETY Data Sheet | EMERGENCY PHONE NUMBER | HAZARD RATING 4= EXTREME 3= HIGH 2= MODERATE 1= SLIGH 0= INSIGNIFICANT **SEE SECTION V |  |
| | 800-346-9090 | | |

I. General Information

| | | | |
|---------------------------|--|------------------------|---|
| Manufacturer | ULTRASEAL INTERNATIONAL, INC. 1100 N. WILCOX AVENUE LOSANGELES, CA 90038 | Trade Names & Synonyms | ULTRASEAL TIRE SEALANT - P/N's 4511/ 4150/4110 and 4110T |
| DOT Hazard Classification | NOT HAZARDOUS | Chemical Family | MIXTURE |
| Proper DOT Shipping Name | COMPOUND, FLUID, NOIBN | | |
| Prepared By: | D.C. ATKINS & SON, INC. | LEGEND: | N/E = Not Established N/A = Not Applicable |
| Date: | JANUARY 1, 2008 | | |

II. Ingredients

| Hazardous Components | CAS Number | Percent | ACGTH TLV |
|----------------------|------------|---------|-----------|
| ETHYLENE GLYCOL | 107-21-1 | <30 | 50 ppm |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

III. Physical Data

| | | | |
|--------------------------------------|-------------------------------------|--|-------------------|
| Boiling Point (deg. F): | 121-127°C, (250-260°F) | Specific Gravity (H ₂ O=1): | 1.08 |
| Vapor Pressure (mm Hg @ 20°C (68°F): | < 20 mmHg | Percent Volatile: | 92 |
| Vapor Density (Air=1): | 1.3 | Evaporation Rate (water=1): | Approximately 1.0 |
| Solubility in Water: | Approximately 90% soluble | Reactivity in Water: | NONE |
| Appearance & Odor: | VISCOUS FIBER SUSPENSION, MILD ODOR | pH: | 8.5-9.0 |

IV. Fire & Explosion Hazard Data

| | | | | |
|-----------------------------------|---|---------------------------|--------|--------|
| Flash Point (Test Method) | SetaFlash Closed Tester > 200 F. | Flammable Limits | UEL NE | LEL NE |
| | | Auto Ignition Temperature | NE | |
| Extinguishing Media | <input checked="" type="checkbox"/> Foam <input type="checkbox"/> Alcohol Foam <input checked="" type="checkbox"/> CO ₂ <input type="checkbox"/> Dry Chemical <input checked="" type="checkbox"/> Water Spray <input checked="" type="checkbox"/> Water <input type="checkbox"/> Not Applicable <input type="checkbox"/> Other | | | |
| Special Fire Fighting Procedures: | NONE | | | |
| Unusual Fire & Explosion Hazards | NONE | | | |

V. Health Hazard Data

| | | | |
|----------------------------------|----------|-----------------------------|--------------------------|
| Threshold Limit Value of Product | OSHA TEV | ACGTH TLV See Section II | Carcinogen NONE KNOWN |
|----------------------------------|----------|-----------------------------|--------------------------|

SYMPTOMS OF EXPOSURE AND ROUTES OF
 EYES: IRRITATION
 SKIN: POSSIBLE IRRITATION ON PROLONGED CONTACT
 INHALATION: IRRITATION TO RESPIRATORY TRACT
 INGESTION: IRRITATION TO THE GASTROINTESTINAL TRACT

FIRST-AID MEASURES
 EYES: FLUSH WITH WATER FOR 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS
 SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND FOOTWEAR
 INHALATION: REMOVE TO FRESH AIR
 INGESTION: GIVE TWO GLASSES OF WATER. INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY

VI. Reactivity Data

| | | | |
|--------------------------|---|----------------|-------------------------|
| Stability | | Unstable | Conditions to Avoid |
| | X | Stable | |
| Incompatibility | | | Materials to Avoid NONE |
| Hazardous Polymerization | | May Occur | Conditions to Avoid NA |
| | X | Will Not Occur | |

Hazardous Decomposition Products OXIDES OF CARBON ON INCINERATION

VII. Environmental Protection Procedures

Spill Response SMALL SPILL: WIPE UP
 LARGE SPILL: DIKE AREA. PUMP INTO TANK FOR RECOVERY OR DISPOSAL.

Waste Disposal Method INCINERATE IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

VIII. Special Protection Information

| | |
|---|--|
| Eye Protection NOT NORMALLY NEEDED | Skin Protection NOT NORMALLY NEEDED |
| Respiratory Protection (Specific Type) NOT NORMALLY NEEDED | Ventilation Recommended GENERAL |
| Other Protection MATERIAL IS SLIPPERY | |

IX. Special Precautions

Hygienic Practices in Handling & Storage STORE INDOORS

OTHER PRECAUTIONS KEEP CLOSURES ON CONTAINERS WHEN NOT IN USE.

DISPOSAL OF EMPTY CONTAINERS FLUSH WITH WATER BEFORE DISPERSING. SHELF LIFE IS 5 YEARS.